

ER 高速小徑刀把

ER HIGH SPEED SLIM COLLET CHUCK



Including pull stud and balancing.
附拉桿，動平衡。

Balancing / 動平衡	Dimensions / 尺寸標示
<p>Option / 選配</p> <p>G2.5</p> <p>Max. 30,000 RPM Or U ≤ 1gmm</p>	

Order No. 訂購編號	FIG	Range 夾持範圍	ød	øD	L	L1	page.115 Pull Stud 拉桿	page.147 Nut 螺帽	page.120 Collet 筒夾	page.148 Wrench 扳手 A	page.148 Wrench 扳手 B
ISO20	ER16-035MS	1	0.6~10.0	22	35	26	PSD-PI20T-42	CAP-ER16MS	ER16	PHS-ER16MS	PHS-ISO20
ISO25	ER16-035MS	1	0.6~10.0	22	35	26.2	PSD-PI25T-42	CAP-ER16MS	ER16	PHS-ER16MS	PHS-ISO25
	ER20-035MS	1	0.6~13.0	28	35	26.2	PSD-PI25T-42	CAP-ER20MS	ER20	PHS-ER20MS	PHS-ISO25
ISO30	ER16-060MS	2	0.6~10.0	22	60	40.9	PSD-PI30T-42	CAP-ER16MS	ER16	PHS-ER16MS	-
	ER25-060MS	2	0.6~16.0	35	60	40.9	PSD-PI30T-42	CAP-ER25MS	ER25	PHS-ER25MS	PHS-ISO30

Applications / 應用

