

THER 小徑刀把 THER SLIM COLLET CHUCK



Balancing / 動平衡	Dimensions / 尺寸標示
<p>G6.3 Max.25,000 RPM Or U ≤ 1gmm</p> <p>Option / 選配 G2.5 Max.25,000 RPM Or U ≤ 1gmm</p>	

Order No. 訂購編號	Range 夾持範圍	ød	ød1	ød2	L	L1	L2	Tool Clamping Depth L3 刀具夾持深度	page.146	page.144	page.120	page.149
									Nut 螺帽	Screw 調整螺絲	Collet 筒夾	Wrench 扳手
HSK50A	THER11-100	1.0~7.0	16	20.6	100	74	69.2	19~48	CAP-THER11	ER-M8	ER11-HP	PHS-20-RO160
	THER16-100	1.0~10.0	22	26.2	100	74	69.2	29~58	CAP-THER16	ER-M11	ER16-HP	PHS-20-RO220
HSK63A	THER11-100	1.0~7.0	16	20.3	100	74	66.3	19~48	CAP-THER11	ER-M8	ER11-HP	PHS-20-RO160
	THER11-130	1.0~7.0	16	22.9	130	104	96.3	19~48	CAP-THER11	ER-M8	ER11-HP	PHS-20-RO160
	THER11-160	1.0~7.0	16	25.5	160	134	126.3	19~48	CAP-THER11	ER-M8	ER11-HP	PHS-20-RO160
	THER16-100	1.0~10.0	22	26.2	100	74	69.2	29~58	CAP-THER16	ER-M11	ER16-HP	PHS-20-RO220
	THER16-130	1.0~10.0	22	28.8	130	104	99.2	29~58	CAP-THER16	ER-M11	ER16-HP	PHS-20-RO220
	THER16-160	1.0~10.0	22	31.4	160	134	129.2	29~58	CAP-THER16	ER-M11	ER16-HP	PHS-20-RO220

Remarks / 備註

- 需配合 3μ HP 筒夾 With 3μ HP Grade Collet
- 若需搭配中心出水管，請參考 page.145 規格表
- 若需出水型刀把，請參考 page.26 選用說明
- 筒夾夾持為一對一整數值

Applications / 應用

