

ER 高速鋼珠螺帽刀把 ER COLLET CHUCK WITH HIGH SPEED BEARING NUT



Balancing / 動平衡	Dimensions / 尺寸標示
<p>G6.3 Max.25,000 RPM Or U ≤ 1gmm</p> <p>Option / 選配 G2.5 Max.25,000 RPM Or U ≤ 1gmm</p>	

Order No. 訂購編號	FIG	Range 夾持範圍	Range ød		L	L1	Tool Clamping Depth L2 刀具夾持 深度	L3	Nut 螺帽	Screw 調整螺絲	Collet 筒夾	Wrench 扳手	
			ød1	ød2									
HSK50A	ER16-100BR	1	1.0~10.0	32	-	100	74	29~58	-	CAP-ER16BR	ER-M11	ER16-HP	PHS-ER16B
	ER32-100BR	1	2.0~20.0	51	-	100	74	41~56	-	CAP-ER32BR	ER-M22	ER32-HP	PHS-ER32
HSK63A	ER16-100BR	2	1.0~10.0	32	50	100	74	29~58	64	CAP-ER16BR	ER-M11	ER16-HP	PHS-ER16B
	ER16-160BR	2	1.0~10.0	32	50	160	134	29~58	120	CAP-ER16BR	ER-M11	ER16-HP	PHS-ER16B
	ER25-100BR	1	1.0~16.0	43	-	100	74	35~55	-	CAP-ER25BR	ER-M18	ER25-HP	PHS-ER25
	ER25-160BR	1	1.0~16.0	43	-	160	134	35~55	-	CAP-ER25BR	ER-M18	ER25-HP	PHS-ER25
	ER32-100BR	1	2.0~20.0	51	-	100	74	41~55	-	CAP-ER32BR	ER-M22	ER32-HP	PHS-ER32
	ER32-160BR	1	2.0~20.0	51	-	160	134	41~78	-	CAP-ER32BR	ER-M22	ER32-HP	PHS-ER32
HSK100A	ER16-100BR	1	1.0~10.0	32	-	100	71	29~58	-	CAP-ER16BR	ER-M11	ER16-HP	PHS-ER16B
	ER16-160BR	1	1.0~10.0	32	-	160	131	29~58	-	CAP-ER16BR	ER-M11	ER16-HP	PHS-ER16B
	ER25-100BR	1	1.0~16.0	43	-	100	71	35~53	-	CAP-ER25BR	ER-M18	ER25-HP	PHS-ER25
	ER25-160BR	1	1.0~16.0	43	-	160	131	35~73	-	CAP-ER25BR	ER-M18	ER25-HP	PHS-ER25
	ER32-100BR	1	2.0~20.0	51	-	100	71	41~49	-	CAP-ER32BR	ER-M22	ER32-HP	PHS-ER32
	ER32-160BR	1	2.0~20.0	51	-	160	131	41~78	-	CAP-ER32BR	ER-M22	ER32-HP	PHS-ER32

Remarks / 備註

- 需配合 3μ HP 筒夾 With 3μ HP Grade Collet
- 若需搭配中心出水管，請參考 page.145 規格表
- 若需出水型刀把，請參考 page.26 選用說明

Applications / 應用

