

THER 小徑刀把

THER SLIM COLLET CHUCK



Balancing / 動平衡	Dimensions / 尺寸標示
HSK25E U ≤ 1gmm HSK32E U ≤ 1gmm	

page.146

page.120

page.149



Order No. 訂購編號	Range 夾持範圍	ød	ød1	L	L1	Tool Clamping Depth L2 刀具夾持深度	Nut 螺帽	Collet 筒夾	Wrench 扳手
HSK25E	THER16-043	0.6~10.0	22	43	33	max32	CAP-THER16	ER16-HP	PHS-20-RO220
HSK32E	THER16-060	0.6~10.0	22	76	40	max40	CAP-THER16	ER16-HP	PHS-20-RO220

Remarks / 備註

- 需配合 3μ HP 筒夾 With 3μ HP Grade Collet
- 筒夾夾持為一對一整數值

Applications / 應用



Drilling
鑽孔



Reaming
鉸孔



Endmilling
銑削



Tapping
攻牙



Mini Diameter
小徑加工

ER 高速小徑刀把

ER HIGH SPEED SLIM COLLET CHUCK



Balancing / 動平衡	Dimensions / 尺寸標示
HSK25E U ≤ 1gmm HSK32E U ≤ 1gmm	

page.147

page.120

page.148



Order No. 訂購編號	Range 夾持範圍	ød	ød1	L	L1	Tool Clamping Depth L2 刀具夾持深度	Nut 螺帽	Collet 筒夾	Wrench 扳手
HSK25E	ER16-043MS	0.6~10.0	22	43	33	max32	CAP-ER16MS	ER16	PHS-ER16MS
HSK32E	ER16-060MS	0.6~10.0	22	60	40	max40	CAP-ER16MS	ER16	PHS-ER16MS
	ER20-060MS	1.0~10.0	28	60	40	max38	CAP-ER20MS	ER20	PHS-ER20MS

Applications / 應用



Drilling
鑽孔



Endmilling
銑削



Tapping
攻牙



Mini Diameter
小徑加工