



PFK 高速全圓螺帽刀把

PFK HIGH SPEED COLLET CHUCK WITH ROUND NUT



BT JIS B6339 (MAS 403 BT)

Dimensions / 尺寸標示

G6.3
BT30 / BT40
Max.25,000 RPM
Or U ≤ 1gmm

G6.3
BT50
Max.20,000 RPM
Or U ≤ 1gmm

Dimensions / 尺寸標示

Order No. 訂購編號	FIG	Range 夾持範圍	ød	ød1	ød2	L	L1	L2	Tool Clamping Depth L3 刀具夾持 深度	page.147 Nut 螺帽	page.144 Screw 調整螺絲	page.117 Collet 筒夾	page.149 Wrench 扳手
BT30 (BTT30)	PFK10-060S	2	1.75~10.0	27.5	27.5	60	38	-	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-090S	2	1.75~10.0	27.5	27.5	90	68	-	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-120S	2	1.75~10.0	27.5	27.5	120	98	-	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK16-060S	2	2.75~16.0	40	40	60	38	-	40~54	CAP-PFK16S	PFK-M12	SK16-P	PHS-20-RO400
	PFK16-090S	2	2.75~16.0	40	40	90	68	-	40~70	CAP-PFK16S	PFK-M12	SK16-P	PHS-20-RO400
PFK16-120S	2	2.75~16.0	40	40	120	98	-	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400	
BT40 (BTT40)	PFK10-060S	2	1.75~10.0	27.5	27.5	60	33	-	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-090S	2	1.75~10.0	27.5	27.5	90	63	-	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-120S	1	1.75~10.0	27.5	32	120	93	70	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-150S	1	1.75~10.0	27.5	32	150	123	70	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK16-060S	2	2.75~16.0	40	40	60	33	-	50~65	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400
	PFK16-090S	2	2.75~16.0	40	40	90	63	-	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400
	PFK16-120S	2	2.75~16.0	40	40	120	93	-	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400
PFK16-150S	2	2.75~16.0	40	40	150	123	-	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400	
BT50 (BTT50)	PFK10-105S	2	1.75~10.0	27.5	27.5	105	67	-	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-135S	1	1.75~10.0	27.5	32	135	97	70	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK10-165S	1	1.75~10.0	27.5	32	165	127	75	30~50	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK16-105S	2	2.75~16.0	40	40	105	67	-	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400
	PFK16-135S	2	2.75~16.0	40	40	135	97	-	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400
PFK16-165S	1	2.75~16.0	40	50	165	127	90	40~70	CAP-PFK16S	PFK-M18	SK16-P	PHS-20-RO400	

Remarks / 備註
 • 需配合 3μ P 筒夾 With 3μ P Grade Collet

Applications / 應用

Drilling
鑽孔

Reaming
鉸孔

Endmilling
銑削

Tapping
攻牙