



PFK 高速全圓螺帽刀把

PFK HIGH SPEED COLLET CHUCK WITH ROUND NUT



| Balancing / 動平衡 | | Dimensions / 尺寸標示 | |
|--|--|-------------------|--|
| G6.3 SK40 Max.25,000 RPM Or U ≤ 1gmm | G6.3 SK50 Max.20,000 RPM Or U ≤ 1gmm | | |
| Option / 選配 G2.5 SK40 Max.25,000 RPM Or U ≤ 1gmm | Option / 選配 G2.5 SK50 Max.20,000 RPM Or U ≤ 1gmm | | |

| Order No. 訂購編號 | FIG | Range 夾持範圍 ød | ød1 | ød2 | L | L1 | L2 | Tool Clamping Depth L3 刀具夾持 深度 | page.147 Nut 螺帽 | page.144 Screw 調整螺絲 | page.117 Collet 筒夾 | page.149 Wrench 扳手 | Applications / 應用 | | |
|-------------------|------------|---------------------|-----------|------|------|-----|-----|--|-----------------------|---------------------------|--------------------------|--------------------------|-------------------|--------------|---------|
| | | | | | | | | | | | | | 30~50 | PHS-10-TW275 | |
| SK40 | PFK10-090S | 2 | 1.75~10.0 | 27.5 | 27.5 | 90 | 71 | - | 30~50 | CAP-PFK10S | PFK-M12 | SK10-P | PHS-10-TW275 | Drilling | Reaming |
| | PFK10-120S | 1 | 1.75~10.0 | 27.5 | 32 | 120 | 101 | 70 | 30~50 | CAP-PFK10S | PFK-M12 | SK10-P | PHS-10-TW275 | Endmilling | Tapping |
| | PFK16-090S | 2 | 2.75~16.0 | 40 | 40 | 90 | 71 | - | 40~70 | CAP-PFK16S | PFK-M18 | SK16-P | PHS-20-RO400 | | |
| | PFK16-120S | 2 | 2.75~16.0 | 40 | 40 | 120 | 101 | - | 40~70 | CAP-PFK16S | PFK-M18 | SK16-P | PHS-20-RO400 | | |
| SK50 | PFK10-105S | 1 | 1.75~10.0 | 27.5 | 32 | 105 | 86 | 70 | 30~50 | CAP-PFK10S | PFK-M12 | SK10-P | PHS-10-TW275 | | |
| | PFK10-135S | 1 | 1.75~10.0 | 27.5 | 32 | 135 | 116 | 70 | 30~50 | CAP-PFK10S | PFK-M12 | SK10-P | PHS-10-TW275 | | |
| | PFK10-165S | 1 | 1.75~10.0 | 27.5 | 32 | 165 | 146 | 75 | 30~50 | CAP-PFK10S | PFK-M12 | SK10-P | PHS-10-TW275 | | |
| | PFK16-105S | 2 | 2.75~16.0 | 40 | 40 | 105 | 86 | - | 40~70 | CAP-PFK16S | PFK-M18 | SK16-P | PHS-20-RO400 | | |
| | PFK16-165S | 1 | 2.75~16.0 | 40 | 50 | 165 | 146 | 95 | 40~70 | CAP-PFK16S | PFK-M18 | SK16-P | PHS-20-RO400 | | |

Remarks / 備註
 • 需配合 3μ P 筒夾 With 3μ P Grade Collet



SK DIN 69871